

Limiting Behavior in Large Networks


PJ Wolfe

Chair of Statistics
Royal Society Research Fellow
University College London

IISc Workshop on High Dimensional Network Analytics
Bangalore, India, 19 December 2013

How do we draw conclusions from and about networks?

Figure 1. The Global Banking Network





IMF Stability Assessment: Size + Interconnectedness \Rightarrow "Importance"?



Statistical network modeling allows us to understand **big data**

Ingredients

- ① Mechanisms that generate data
- ② **Structure** that facilitates analysis
- ③ **Tools** that can be understood



Objects + relationships \Rightarrow
networks






A network is two sets:

- **Nodes** ('nouns'): any discrete set of objects
- **Links** ('verbs'): a set of pairs of these objects

Examples:

- Social networks: people, friendships
- Complex systems: variables, correlations
- Images: pixel locations, similarities




Adjacency matrices enable visualization of large networks:

$$(i,j)\text{th entry} = \begin{cases} 1 & \text{if node } i \text{ links to node } j, \\ 0 & \text{otherwise.} \end{cases}$$


Their structure reveals information:

- Links as (biased) coin tosses
- How to couple the tosses?



Decoupled coin tosses

- Links as repeated tosses of the same coin, $\Pr(\text{Heads} = \frac{1}{100})$
- **How many connections** will form as the network grows?
- Emergence of **triangles** or other structure?






Strongly coupled coin tosses

- Random scattering of nodes
- Nodes connect to others **nearby**
- As the network grows, will it eventually become **connected**?


Cluster models

- Suppose n network nodes divide into k 'regular' groups (Szemerédi, Gowers, Tao)
- **Thm:** If k grows like \sqrt{n} , with edges added faster than n grows, then we can recover groups



Graph limits


- Suppose a network is like a noisy 'image' f in the infinite limit (digital \rightarrow analog)
- **Thm:** As $n \rightarrow \infty$, network yields 'oracle' information on f at a rate of at least $n^{-1/4}$
- Brute force algorithms needed to reveal this information... but many special cases possible




Political blog network (Adamic, 2005)

- What is the network equivalent of clustering?
- If the data are not generated by a cluster model, can we still approximate the generating mechanism (nonparametrics)?
- How to establish correct interpretation for nonparametrics?


Survey data on high-school friendships (Add Health, 1994):



students grouped by
year (black lines)



students grouped by
race (blue lines)




by race (blue lines) and
then clustered (red)

Implication: how do we interpret the notion of “clusters”?

- Assume the network to be generated nonparametrically, and then fit via likelihood-based clustering
- The resulting estimate approaches an optimal piecewise-constant approximation to the generative model


Implication: significantly broadens the interpretation of “clusters”:




Example: Lovasz, *Very Large Graphs* (AMS, 2012):



Generative model




Adjacency matrix



- 1 Specify $\underline{\omega} : [0, 1]^3 \rightarrow [0, 1]$
- 2 Generate latent variable $\alpha \sim \text{Uniform}(0, 1)$
- 3 Generate latent variables $\xi = (\xi_1, \dots, \xi_m)$ and $\zeta = (\zeta_1, \dots, \zeta_n) \sim \text{Uniform}(0, 1)$
- 4 Let A_{ij} be Bernoulli with parameter $\omega_\alpha \equiv \underline{\omega}(\alpha, \xi_i, \zeta_j)$. Connect nodes i and j if $A_{ij} = 1$.

Qn: Can we fit a piecewise-constant approximation, ω_ϕ , to ω_α ?



Parameters $\phi \equiv (\mu, \nu, \theta)$ describe ω_ϕ :

- Vectors μ, ν : boundaries of the piecewise-constant regions
- Matrix θ : heights of the piecewise-constant regions

We can fit $\phi = (\mu, \nu, \theta)$ to an observed adjacency matrix A by various criteria:

$$\text{Likelihood: } L_A(\mu, \nu, \theta) = \max_{S, T} \sum_{i, j} \log \mathbb{P}(A_{ij} \mid \theta_{S(i)T(j)})$$

$$\text{Mean-squared error: } R_A(\mu, \nu, \theta) = \min_{S, T} \sum_{i, j} |A_{ij} - \theta_{S(i)T(j)}|^2$$

Mappings S and T assign nodes to K clusters, and are constrained to have assignment proportions matching μ and ν .

Fitting criteria correspond to risk functionals that measure agreement with an equivalence class induced by the unknown ω .

Let Π be the set of all measure-preserving bijective maps of $[0, 1]$ to itself. Then we can minimize mean-squared error:

$$R_{\omega}(\phi) = \inf_{\pi_1, \pi_2 \in \Pi} \iint_{(0,1)^2} |\omega(\pi_1(x), \pi_2(y)) - \omega_{\phi}(x, y)|^2 dx dy,$$

or maximize the corresponding likelihood as

$$\begin{aligned} L_{\omega}(\phi) = \sup_{\pi_1, \pi_2 \in \Pi} \iint_{(0,1)^2} & [\omega(\pi_1(x), \pi_2(y)) \log \omega_{\phi}(x, y) \\ & + \{1 - \omega(\pi_1(x), \pi_2(y))\} \log \{1 - \omega_{\phi}(x, y)\}] dx dy. \end{aligned}$$

For the least squares co-blockmodel M-estimator

$$\hat{\phi} = \operatorname{argmin}_{\phi \in \Phi} \left\{ \min_{S \in \mathcal{Q}_{\mu}^m, T \in \mathcal{Q}_{\nu}^n} \frac{1}{mn} \sum_{i=1}^m \sum_{j=1}^n |\theta_{S(i)T(j)} - A_{ij}|^2 \right\}$$



relative to the L^2 risk

$$R_{\omega}(\phi) = \sup_{\pi_1, \pi_2 \in \Pi} \iint_{(0,1)^2} |\omega(\pi_1(x), \pi_2(y)) - \omega_{\phi}(x, y)|^2 dx dy,$$

we have that

$$R_{\omega}(\hat{\phi}) - \inf_{\phi \in \Phi} R_{\omega}(\phi) = \mathcal{O}_P(n^{-1/4}).$$

An analogous result holds for $\sup_{\phi \in \Phi} L_{\omega}(\phi) - L_{\omega}(\hat{\phi})$.





Graph limits

- Suppose a network is like a noisy 'image' f in the infinite limit (digital \rightarrow analog)
- **Thm:** As $n \rightarrow \infty$, network yields 'oracle' information on f at a rate of at least $n^{-1/4}$
- Brute force algorithms needed to reveal this information... but many special cases possible

Cluster models

- Suppose n network nodes divide into k 'regular' groups (Szemerédi, Gowers, Tao)
- **Thm:** If k grows like \sqrt{n} , with edges added faster than n grows, then we can recover groups





Page 2: Figure 1 from *Integrating Stability Assessments Under the Financial Sector Assessment Program into Article IV Surveillance: Background Material*, Prepared by the Monetary and Capital Markets Department, August 27, 2010.

Page 3: www1.cs.columbia.edu/~sara/cs6998/enron11-29-00m10.jpg;
www.carlmaples.com/Enron_building_1893.html.

Page 6: Miller, B. A., Bliss, N. T., and Wolfe P. J., "Toward signal processing theory for graphs and non-Euclidean data," in Proceedings of the IEEE International Conference on Acoustics, Speech, and Signal Processing (2010).

Page 8: Newman, M. E. J. "Communities, modules and large-scale structure in networks." *Nature Physics* (2011): 25-31; Faculty of Physics and Astronomy, U. Würzburg, www.physik.uni-wuerzburg.de/typo3temp/pics/858ca46225.jpg;
Copyright Channel Four Television Corporation

Page 9: <http://en.wikipedia.org/wiki/File:Centrality.svg>